Fig.1

101 receiving portion

102 navigation message analyzing portion

103 almanac storing portion

104 ephemeris storing portion

105 clock portion

106 satellite position calculating portion

107 position measuring portion

10/516625

図2

Fig.2

START

S201 — WNaを受信済みか？

S202 — WNの値を WNaの値として予測する

S203 — 予測したWNaの値を用いて アルマナックを復元

S204 — アルマナックを保存部に保存

END

S201 WNa has been already received ?

S202 predict a WN value as a WNa value

S203 restore an almanac by using the predicted WNa value

S204 store in an almanac storing portion

図3

Fig 3

START

S301 天チ

S301 WNaを受信
済みか

S302 時計部105の現在時刻
より週番号を算出せよ

S303 週番号をWNa2から値に8WNaの値に補正し
フルマナックを復元

S304 アルマナックを保存部に保存せよ

END

S301 WNa has already been received ?

S302 calculate a week number based on a current time of a clock portion 105

S303 predict the week number as a WNa value and restore an almanac

S304 store in an almanac storing portion

S401 calculate a week number and a time lapsed from a head of the week

based on a current time of a clock portion 105

S402 a difference between the received Z count and the calculated time

lapsed from a head of the week exceeds a threshold value ?

S403 decide that an almanac which is restored based on the predicted WNa is

abnormal

S404 abandon

S405 decide that an almanac which is restored based on the predicted WNa is

valid

S406 store in an almanac storing portion

Fig. 4 図

START

S401 時刻部105の現在時刻より週番号と週の先頭からの経過時間を算出

S402 受信したZカウントと算出した週の先頭からの経過時間との差が閾値を超えるか？

S403 予測したWNaを基に復元したアルマナックが異常と判断

S404 破棄

S405 予測したWNaを基に復元したアルマナックが正常と判断

S406 アルマナック格納部に格納

END

Y   N

A501 The almanac is stored ?

S502 calculate a satellite position by using the almanac which is stored

S503 calculate a satellite position by using the almanac which is restored based

on the predicted WNa

A504 a positional difference between them exceeds a threshold value ?

A505 decide that an almanac which is restored based on the predicted WNa is

abnormal

S506 abandon

S507 decide that an almanac which is restored based on the predicted WNa is

valid

S508 store in an almanac storing portion

図5

Fig. 5

10/516625

S601 a signal of a certain satellite is received ?

S602 measure a Doppler-shift frequency of the signal being received

S603 calculate the Doppler-shift frequency of the certain satellite by using the

almanac which is restored based on the predicted WNa

S604 a positional difference between them exceeds a threshold value ?

S605 decide that an almanac which is restored based on the predicted WNa is

abnormal

S606 abandon

S607 decide that the almanac which is restored based on the predicted WNa is

valid

S608 store in an almanac storing portion

Fig. 9

6/13

BEST AVAILABLE COPY

10/516625

S701 The almanac is stored ?

S702 calculate a satellite position S0 by using the almanac which is stored

S703 calculate WNa, WNa+1, WNa-1 based on the predicted WNa

S704 restore three almanacs based on WNa, WNa+1, WNa-1 respectively

S705 calculate satellite positions S1, S2, S3 by using three restored almanacs respectively

S706 decide the almanac which calculates the satellite position closest to S1 as a valid almanac

S707 store in an almanac storing portion

図7 Fig. 7

7/13

S801 a signal of a certain satellite is received ?

S802 measure a Doppler-shift frequency F0 of the signal being received

S803 calculate WNa, WNa+1, WNa-1 based on the predicted WNa

S804 restore three almanacs based on WNa, WNa+1, WNa-1 respectively

S805 calculate three Doppler-shift frequencies F1, F2, F3 by using three restored almanacs

S806 decide the almanac that calculates the Doppler-shift frequency closest to F0 as a valid almanac

S807 store in an almanac storing portion

図 Fig. 8

START

スタート

S801 ある衛星の信号を受信しているか

Y / N

S802 受信している信号のドップラー周波数F0を測定

S803 予測したWNaを基に WNa, WNa+1, WNa-1を算出

S804 WNa, WNa+1, WNa-1を基にそれぞれ3種類のアルマナックを復元

S805 復元した3種類のアルマナックで3つのドップラー周波数F1,F2,F0を算出

S806 F0にもっとも近いドップラーシフト周波数を算出したアルマナックを正しいアルマナックと判定

S807 アルマナック保存部に保存

END

S901 WN, Z count already is received ?

S902 calculate a time T based on WN and Z count

S903 calculate an epoch of the almanac based on predicted WNa and Toa

S904 T0−T>3.5 days ?

S906 T0−T<−3.5 days ?

S908 store in an almanac storing portion

図9 Fig.9

START

S901 WNA・Zカウント 受信済みか

S902 WN及びZカウントから 時刻Tを算出

S903 予測したWNa及びびToaを基に アルマナックの元期Tを算出

S904 T0−T>3.5日か

S905 WNa＝WNa−1

S906 T0−T<−3.5日か

S907 WNa＝WNa＋1

S908 アルマナック保持部に保存

END

9/13

10/516625

Fig. 10

START

S1001

受信したToaに対応するWNaを算出済みか

N

Y

S1002

算出済みのWNaを使用してアルマナックを算出

S1004

WNaを予測してアルマナックを復元

S1003

アルマナックをアルマナック保存部に保存

S1005

Toa、復元したアルマナックをアルマナック保存部に保存

END

S1001 WNa corresponding to received Toa is calculated ?

S1002 calculate an almanac by using the calculated WNa

S1003 store the almanac in an almanac storing portion

S1004 restore the almanac by predicting WNa

S1005 store Toa and the restored almanac in an almanac storing portion

10/13　　BEST AVAILABLE COPY

10/516625

図11　Fig.11

START

S1101

エフェメリスを
受信したか

S1102

受信したエフェメリスを基に
アルマナックを作成

S1103

アルマナックを
アルマナック保存部に保存

END

S1101 Ephemeris is received ?

S1102 form an almanac based on received ephemeris

S1103 store the almanac in an almanac storing portion

BEST AVAILABLE COPY

Fig. 12

図十三   Fig. 13

1 receiving portion

2 navigation message analyzing portion

3 almanac temporarily-storing portion

4 almanac storing portion

5 ephemeris storing portion

6 clock portion

7 satellite position calculating portion

8 position measuring portion